



Primer

Sealing Primer suitable for wet rooms

For sealing and protection of moisture sensitive, absorbent surfaces prior to tanking and fixing ceramic tiles.

- For interior and exterior use
- Ideal moisture barrier
- For priming of absorbent surfaces
- Quick drying
- Approved for wet rooms

Product

Polymer dispersion added pink tracer

Coverage

Substrate	Coverage undiluted Primer, litre/m ²
Absorbent surfaces, such as render, brickwork, concrete, light-weight concrete	Approx. 0.10
Paperfaced plasterboards, fibre-reinforced plasterboards	Approx. 0.15
Gypsum plaster, plywood 2 applications	Approx. 0.20

Packaging

Available in 4 litres and 10 litres plastic container.

Surfaces

Cement/sand rendering, 2 days
 Concrete, older than 28 days, max 90% relative humidity.
 Light-weight concrete, max. moisture content 8%
 Aerated concrete, brickwork, plasterboards.
 Screed, older than 14 days, max 90% relative humidity.
 Plywood on floors, moisture content 7 - 12%.
 Flooring containing cement-based levelling compound
 Gypsum plaster and anhydrite floors, max. moisture content 1%

Application

The surface should be dimensionally stable, sound, and clean. Free from laitance, grease, and dust. There should be no blooms or crack formations. Residues from grease or soap can be removed with **Alfix Deep Cleaner**. Apply Alfix Primer to the surface with large brush or roller to full coverage. Rendering, brickwork, concrete, light-weight concrete, aerated concrete, and cement-based levelling compounds should be primed with Primer diluted with water 1:1. Plywood, gypsum plaster, and anhydrite floors should be primed with 2 applications. Apply first coat diluted with water 1:3, apply second coat undiluted. Paperfaced plasterboards and fibre-reinforced plasterboards should be primed undiluted to full coverage. If boards are foil-backed, apply only 1 coat of primer diluted 1:3 with water. Foil-backing eliminates any further need for a waterproof membrane. For exterior applications, dilute primer 1:6 with water.

Tanking

Areas subjected to frequent or high water exposure, so-called wet zones, require subsequent waterproofing with a sealing membrane: **Alfix 1K Sealing Membrane** or **Alfix 2K Sealing Membrane**

Precautions

NONE

Cleaning

Clean residues from tools with water before the primer sets. Once dried, primer can be removed mechanically or with solvent.
Wear protective gloves during work since the product tends to stick to the skin.

Test

Danish SBI

Technical enquiries

Wet rooms – Tanking with Alfix

Product info on:

- **Alfix Deep Cleaner**
- **Alfix 1KSealing Membrane**
- **Alfix 2KSealing Membrane**

Product health and safety data /COSH

For further information, please consult our Technical Services Dept.
For latest update of this product info, visit www.alfix.com.

Technical data

Working temperature	Min. +12°C
Density	1.2 kg/litre
Drying time	1 hour at +20°C
Shelf life	Min. 12 months in unopened container. Keep protected from frost.